

External Harddisc

ONE ONE TECHNOLOGIES

Professional Storage Solutions



www.one-tech.com

A1uDISC
80 GB



ONE TECHNOLOGIES ONE 

AluDISC 80GB



Features

- quality drive inside
- 7.200 rpm
- true Plug & Play interface
- slim and portable
- supports Windows & Mac
- fanless for low noise operation
- compact size aluminium enclosure
- 3 years warranty

Interface	a) FireWire / IEEE-1394a / iLink, (internal ATA-to-FW Bridge OX911) b) USB 2.0 (HiSpeed) (internal ATA-to-USB 2.0 Bridge ISD300) c) Combo FireWire / IEEE-1394a / iLink and USB 2.0 (HiSpeed), (internal ATA-to-FW/-USB 2.0 ComboBridge OX911/ISD300)
Formatted capacity	
Hard disc interface	76,45 GB
Rotational speed	ATA-6/100
Cache	7.200 rpm
Average seek time	2 MB
Data transfer (Host-to-Buffer) / (Typical)	9 ms FireWire 400 Mbit/s / (34 Mbit/s), 24 MB sustained
Features	USB 2.0 480 Mbit/s / (13-18 Mbit/s), 18 MB sustained tagged command queuing, load/unload head ramps, fluid dynamic bearing motors, SMART, portable, AV-comp. and hot-plugable
Connectors	- 2x 6 pin FireWire - 6 pin USB 2.0

Power supply

external 110-240 V, 25 W

Dimensions / Weight

130 mm / 40 mm / 215 mm; ca. 1.060 g

Scope of supply

external drive, FireWire / USB cable, EU-power supply, external
power supply, ONE ToolsCD (with online-manual)

Warranty

3 years

Safety standards

CE

Systems requirements

PC or Mac computer with FireWire or USB port
PC: Win 98SE/ME/2000/XP
Mac: OS 8.6 classic (USB 1.1 only), OS X, Apple FireWire 2.4.4, FW
enabler

Support / Hotline

Germany: +49 (0) 1 90 / 83 93 04 (1,86€/min. dtms)
United Kingdom: +44 (0) 12 23 50 77 00
Denmark: +45 87 45 94 05
Sweden: +46 (0) 8 91 11 94
Norway: +47 22 30 73 00
Finland: +45 87 45 94 05

Germany/Austria/Switzerland: support@one-tech.com
United Kingdom/Skandinavia: support@one-tech.dk

ONE Technologies